

# Coating Application Rates

Version Date 06/2014

Page 1 of 1



## Elasto 46 & 52

Substrate	5 Year (New)	5 Year (Recoat)	10 Year	15 Year
Foam	20 mils 2.5 gal / sq	12 mils 1.5 gal / sq	28 mils 3.5 gal / sq	36 mils 4.5 gal / sq
Metal	16 mils 2.0 gal / sq	12 mils 1.5 gal / sq	20 mils 2.5 gal / sq	24 mils 3.0 gal / sq
Built-Up	24 mils 3.0 gal /sq	16 mils 2.0 gal /sq	28 mils 3.5 gal /sq	36 mils 4.5 gal / sq
Modified Bitumen	24 mils 3.0 gal /sq	16 mils 2.0 gal /sq	32 mils 4.0 gal /sq	40 mils 5.0 gal / sq

## Elasto 58

Substrate	5 Year (New)	5 Year (Recoat)	10 Year	15 Year
Foam	20 mils 2.0 gal / sq	12 mils 1.0 gal / sq	28 mils 3.0 gal / sq	36 mils 4.0 gal / sq
Metal	16 mils 1.5 gal / sq	12 mils 1.0 gal / sq	20 mils 2.0 gal / sq	24 mils 2.5 gal / sq
Built-Up	24 mils 2.5 gal /sq	16 mils 1.5 gal /sq	28 mils 3.0 gal /sq	36 mils 4.0 gal / sq
Modified Bitumen	24 mils 2.5 gal /sq	16 mils 1.5 gal /sq	32 mils 3.5 gal /sq	40 mils 4.5 gal / sq

### Warranty:

Any/all guarantees/warranties for products sold by SunBlock Materials are limited only to those provided in writing and only available to the applicator of the product. The information listed herein is to be used only as a guide and is subject to change without notice. All information contained on this document is believed to be reliable, but may vary to some degree. **NO WARRANTY, EXPRESSED/IMPLIED, INCLUDING FITNESS OF USE, IS MADE BY SUNBLOCK MATERIALS WITH RESPECT TO THE PRODUCTS OR INFORMATION SET HEREIN.** Liability, if any, is limited to replacement of product only.